



PATENT
Attorney Docket No. 9031-1017

IN THE U.S. PATENT AND TRADEMARK OFFICE

In re application of

Warren SMOOK, et al.

Confirmation No.: 7556

Application No. 10/563,462¹

Group Art Unit: Unknown

Filed: January 5, 2006

Examiner: Unknown

Title: **GEAR TRANSMISSION UNIT WITH PLANET CARRIER**

CLAIM TO PRIORITY

Assistant Commissioner for Patents
Washington, DC 20231

Sir:

Applicant herewith claim the benefit of the priority filing date of the following application for the above-entitled U.S. application under the provisions of 35 U.S.C. § 119 and 37 C.F.R. § 1.55:

<u>Country</u>	<u>Application No.</u>	<u>Filed</u>
GREAT BRITAIN	0326933.9	November 19, 2003

Certified copy of the above-noted application is attached hereto.

Respectfully submitted,

YOUNG & THOMPSON

Benoit Castel

Benoit Castel, Reg. No. 35,041
745 South 23rd Street
Arlington, VA 22202
Telephone (703) 521-2297
Telefax (703) 685-0573
(703) 979-4709

BC/pmt
February 9, 2006

THIS PAGE BLANK (USPTO)



32522 0000

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

The undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994; to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1985 under the same name as that with which it was registered immediately before re-registration save for substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Dated 6 January 2006

CERTIFIED COPY OF
PRIORITY DOCUMENT

THIS PAGE BLANK (USPTO)

Patents Form 1/77

Patents Act 1977
(Rule 16)19NOV03 E853443-1 000247
P01/7700 9.00-0326933.9

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form.)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

03414 GB

2. Patent application number

(The Patent Office will fill in this part)

0326933.9

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Hansen Transmissions International NV

Leonardo da Vincilaan 1

B-2650 Edegem

Antwerp

Belgium

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

6354443001

4. Title of the invention

Gear Transmission Unit with Planet Carrier

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Mr J R Badger

Invensys Intellectual Property

P-O Box 8433

Redditch, B98 0DW

United Kingdom

Patents ADP number (if you know it)

8494551001

(51/77 - 19.12.05)

6 Simpson Road
Wylde Green
Sutton Coldfield
West Midlands
B72 1EP

07549520001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

FROM : BADGER

PHONE NO. : 0121 382 5143

19 Nov. 2003 12:37PM P1

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

	0
Continuation sheets of this form	7
Description	2
Claims(s)	1
Abstract	6
Drawing(s)	

10. If you are also filing any of the following, state how many against each item.

	0
Priority documents	0
Translations of priority documents	0
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	
Request for preliminary examination and search (Patents Form 3/77)	0
Request for substantive examination (Patents Form 10/77)	0
Any other documents (please specify)	0

11.

I/We request the grant of a patent on the basis of this application.

Signature

J. R. Badger

Date

19/11/03

12. Name and daytime telephone number of person to contact in the United Kingdom

J R Badger

01527 838264

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

GEAR TRANSMISSION UNIT WITH PLANET CARRIER

This invention relates to a planet carrier for a gear transmission unit and in particular, though not exclusively, to a planetary type gear transmission unit. It may be applied to a gear transmission unit for a wind turbine.

There is a continuing demand for larger wind turbines especially for offshore sites due to scarcity of suitable sites and cost of civil works. At the same time the requirements for reduction of size and weight of the machines and their components become more and more important. Typically a wind turbine rotor drives the low speed shaft of a gear transmission unit, which transforms torque and speed of the rotor to the required torque and speed of an electrical generator.

Integration of the components in a wind turbine is a way to reduce the weight and to make the drive assembly more compact, but it is important that the design and execution of the drive assembly avoids mutual interference of the external and internal loads on the different components. It is also important that the construction of an integrated drive assembly allows effective lubrication to be achieved economically and reliably.

The present invention is directed particularly but not exclusively to the problem of providing an accurate and long life support for planet gears in a manner which is economical and which may be utilized on a wind turbine assembly.

In accordance with one aspect of the present invention a planetary type gear transmission unit comprises sun, planet and ring gears and a planet carrier, said planet carrier comprising a planet bogie plate which supports and locates circumferentially spaced planet gear bearings on which planet gears are mounted, and at least some of said bearings being taper roller type bearings.

The gear unit may comprise planet gears which are arranged in axially aligned pairs. That is, the planet gears of a pair may be co-axially arranged.

The bearings may support respective pairs of aligned planet gears, typically the two gears of each pair being positioned at opposite sides of the plate.

The bearing(s) for each circumferentially spaced planet gear position may be supported on a shaft which in use is able to self adjust in said angular position relative to the bogie plate.

Alternatively said shaft may be substantially rigidly secured to the bogie plate. The bogie plate may be of a kind which, in consequence of elastic deformation, is compliant to an extent sufficient to allow self adjustment of the angular position of the shaft relative to the axis of rotation of the ring gear, for example in the case of a shaft which is substantially rigidly secured to the bogie plate.

As considered in an axial direction parallel with the axis of rotation of the planet carrier, a main bearing for rotatably supporting a ring gear relative to a planet carrier may lie at a position substantially aligned axially with the axial position of at least the ring gear of the gear transmission unit.

In some embodiments of the invention it may be preferred that the sun, planet and ring gears lie in a transverse plane (perpendicular to the rotation axis of said rotational forces) which also contains said main bearing.

The ring gear may provide axial and radial locations for the main bearing. The ring gear may have a radially outer surface of a stepped profile to define a shoulder for axial location of an inner bearing ring of the main bearing. The inner bearing ring may be secured axially and non-rotatably between said shoulder a supporting structure.

The ring gear may be provided with a reinforcing ring, and said reinforcing ring may extend axially and or radially beyond the toothed surface of the ring gear. Said reinforcing ring may provide an axial location of the main bearing.

The main bearing may comprise a double taper bearing, and said double taper bearing may comprise a single outer bearing ring. The double taper bearing may comprise rollers arranged in an O configuration in which the rollers of one series increase in diameter in a direction away from the rollers of the other series of the pair.

In a yet further of its aspects the present invention provides a wind turbine comprising rotors, a generator and a drive assembly comprising a gear transmission unit of a type in accordance with the present invention. In said drive assembly the ring gear typically may be supported non-rotatably relative to supporting structure.

A part of the gear transmission unit, e.g. a housing thereof, may be arranged to support an electrical generator.

The invention will now be described, by way of example only, with reference to the accompanying diagrammatic drawings in which: -

Figure 1 is an elevation view of a wind turbine having a gear transmission unit of the present invention;

Figure 2 is a sectional view of part of a gear transmission unit;

Figure 3 shows part of Figure 2 in more detail, and

Figure 4 shows a particular feature of the present invention.

A wind turbine 10 (see Figure 1) comprises a gear transmission unit 11 which acts to transmit torque from rotor blades 12 and a rotor hub 14 to an electrical generator 13, the gear transmission unit comprising an epicyclic gear unit. The gear transmission unit and generator are housed in and supported by a nacelle 15.

The gear transmission unit 11 is now described in more detail with reference to Figures 2 and 3. The gear transmission unit 11 comprises an epicyclic gear unit having four circumferentially spaced planet gears 25, a sun gear 27 a planet carrier 28, and a ring gear 24 which is non-rotatably mounted relative to the nacelle structure 15.

The sun gear is connected to an output shaft (not shown) which connects either to a further gear unit or direct to the rotor of the generator 13.

The radially outer surface 29 of the ring gear 24 provides location and support for the inner ring 30 of a main bearing 23.

The outer ring 31 of the main bearing has secured thereto the rotor hub 14 and, interposed between the rotor hub and ring 31, the outer region 22 of the planet carrier 28.

In a prior proposed construction the planet carrier 28 of Figure 3 comprises four bearing support studs 26 uniformly circumferentially spaced to locate bearings 32 which rotatably support the four planet gears 25. The planet carrier 28 has an annular region 33 which extends radially between the radial position of the bearing studs 26 and the outer region 22 and is designed to be relatively stiff, in a circumferential direction about the Y axis, for transmission of torque between the region 22 and the bearing studs 26, but to be relatively flexible about the X and Z axis.

In accordance with the present invention the planet carrier 28 is replaced by a planet carrier 41 (see Figure 4) provided, in this embodiment, with three integral and uniformly circumferentially spaced studs 42 which support a planet bogie plate 43. The planet bogie plate 43 provides support for three circumferentially uniformly spaced shafts 44 arranged each (as viewed in the plane of Figure 4) to self adjust in angular position on the plate 43. Each shaft 44 provides support, at opposite sides of the plate 43, for a pair of taper roller

bearings 45, 46 about which each of a pair of planet gears 47, 48 are rotatably mounted for engagement with the ring gear 49.

In the aforescribed construction the torque acting on the rotor hub 14 under action of the rotor blades 12 is transmitted to the planet gears 47, 48 via the planet carrier 41 rotatably mounted at its outer region to the outer ring 31 of bearing 23. Bending moments and axial forces in the Y direction exerted by the rotor hub in this construction are transmitted direct to the bearing 23. The flexibility of the annular portion 33 of the planet carrier 28 assists to substantially isolate those forces from the planet gears.

The present invention thus teaches, in its broadest aspect, that a bogie of a planet carrier is provided with roller bearings which are of the taper type for the support of planet gears.

The present invention teaches in another of its aspects that the planet gears may be supported, via their bearings, on a shaft of the so-called flexpin type, such as described in GB 1,101,131 in the context of a simple type of epicyclic gear. The present invention, in this one of its aspects, perceives that special benefit may be achieved by utilising a shaft of the flexpin type in the context of an epicyclic gear unit having a planet bogie. This benefit may be attained irrespective of whether, as described above, the planet gear bearings are taper roller bearings, or whether they are cylindrical roller bearings. Use in constructions having other bearing arrangements, and such as spherical bearings, is not excluded.

A variation of the Figure 4 construction to utilise a flexpin as the shaft 44 thereof is now discussed in more detail.

Figure 5 shows the basic layout. The back-plate 5, i.e. bogie plate, drives the inner part of the planet shaft 1 which in turn carries the outer part or sleeve (4), the planet bearing 2 and the planet 3. The function of the flexpin in the context of application to a bogie is now described briefly with reference to Figure

6. An external force (for instance the tangential planet forces) will cause the inner shaft 1 to bend as a result of the bending moment $F \cdot y$. Point "A" is offset by a distance "x" from the application point of the force causing a moment $F \cdot x$. This bending moment at "A" works in the opposite direction to the first one and thus causes the outer sleeve to counter rotate in the direction of the second moment.

The amount of compensation will depend upon the distances x and y as well as the designs of the inner shaft and sleeve. The use of the flexpin is advantageous for load distribution over the tooth flanks (KH β) as well as load sharing between the planets in the planetary cell (K γ). The equality of loads between the planets (K γ) will be inversely proportional to the stiffness of the planet shafts and it is thus preferred to make the planet shafts as flexible as possible.

The amount of compensation could be equal at both sides of the central bogie plate but does not have to be. Particularly if the gear unit comprises a helical sun gear it may be advantageous to choose different amounts of compensation in order for the left and right planets to better follow the helical deformation of the sun shaft under load. (Due to torsion). This would not be possible in the classical flexpin designs as there is only one row of planets, but is possible in the application to a planet bogie.

When using helical teeth in a planetary cell, a moment is created by the axial components of the normal tooth forces in the ring gear and sun meshes respectively (see Figure 7). This unwanted effect causes the planets to skew and the amount of skewing is inversely proportional to the planet shaft stiffness. With a flexpin design, the planet shaft assembly (inner shaft and sleeve) is less stiff than in conventional designs and will thus cause more planet skewing. This is the reason that the flexpin is usually only used with spur gearing. A possible solution to this problem could come from making the planet shaft (inner or combination)

an-isotropic as far as it's stiffness goes. Figures 8 to 10 show a planetary system employing such a design. The inner shaft is made in such a way as to still allow the needed flexibility in the tangential direction (see Figure 9) but to be as stiff as possible in a plane normal to the tangential direction (Figure 10). In this way it could become possible to use the flexpin in combination with helical teeth.

CLAIMS

1. A planetary type gear transmission unit comprises sun, planet and ring gears and a planet carrier, said planet carrier comprising a planet bogie plate which supports and locates circumferentially spaced planet gear bearings on which planet gears are mounted, and at least some of said bearings being taper roller bearings.
2. A gear transmission unit according to claim 1, wherein it comprises planet gears arranged in axially aligned pairs.
3. A gear transmission unit according to claim 2, wherein the bearings support respective pairs of aligned planet gears.
4. A gear transmission unit according to claim 3, wherein two gears of each pair are positioned at opposite sides of the plate.
5. A gear transmission unit according to any one of the preceding claims, wherein each planet gear of a pair is mounted on a pair of tapered roller bearings.
6. A gear transmission unit according to any one of the preceding claims and comprising a pair of tapered roller bearings arranged in an O configuration.
7. A gear transmission unit according to any one of the preceding claims, wherein the bearings for each circumferentially spaced planet gear position are supported on a shaft which, in use, self adjusts in said angular position relative to the bogie plate.
8. A gear transmission unit according to any one of claims 1 to 6, wherein the bearings for at least some circumferentially spaced planet gear positions are supported on a shaft which is substantially, rigidly secured to the bogie plate.
9. A gear transmission unit according to claim 8, wherein each said shaft is substantially rigidly secured to the bogie plate.
10. A gear transmission unit according to any one of claims 7 to 9, wherein the bogie plate is able to deform elastically to allow self adjustment of the angular position of the or each shaft relative to the axis of rotation of the ring gear.

11. A gear transmission unit according to any one of the preceding claims, wherein the main bearing comprises an inner ring bearing surface of a diameter greater than that of the toothed surface of the ring gear.
12. A gear transmission unit according to any one of the preceding claims wherein the planet carrier provides a radially extending torque transmissions path which is torsionally stiff but relatively compliant in an axial direction parallel with the axis about which the rotational forces act.
13. A gear transmission unit according to any one of the preceding claims, wherein the planet gears are supported relative to the bogie plate by a shaft of the flexpin type.
14. A gear transmission unit according to claim 1, and substantially as hereinbefore described.

10

ABSTRACT

A planetary type gear transmission unit suitable for a wind turbine comprises sun (27), planet (25) and ring (24) gears and a planet carrier (41), the planet carrier comprising a planet bogie plate (43) which supports and locates circumferentially spaced planet gear bearings (45, 46) on which the planet gears are mounted, and at least some of said bearings (45, 46) being taper roller bearings.

JRB/jd - 03410PCT

2/6




FIG. 2

3/6




FIG. 3

4/6









FIG. 4


5/6

RODIE + FLEXPINFIGURE 5FIGURE 6FIGURE 7

6/6

FIG. 8.

FLEXIBLE

FIG. 9

LESS FLEXIBLE

FIG. 10

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)